

























8 INCH SPEAKER SHOWDOWN

MANUFACTURER	DISTRIBUTORS	MODEL NUMBER	IN-WALL/ IN-CEILING	SHAPE	DIMENSIONS	CUT-OUT DIMENSIONS	PAINTABLE FACADE	BEZEL WIDTH	SPEAKER DEPTH	GRILL MATERIAL	SHIPPING WEIGHT	TWEETER	MIDRANGE	WOOFER	FREQUENCY RESPONSE	NOMINAL IMPEDANCE	POWER HANDLING	SENSITIVITY (2.83V @1M)	WARRANTY	
	Amber Technology www.ambertech.com.au www.ambertech.co.nz	AP-CM1008	In-ceiling	Round	Ø244mm	Ø223mm	✓	15mm	90mm	Aluminium	1.1kg	1"		8" polypropylene	50Hz-20kHz	8Ω	100W	90dB	2 years	
		AP-CM1008-BL	In-ceiling	Round	Ø244mm	Ø223mm	✓	15mm	90mm	Aluminium	1.1kg	1"		8" polypropylene	50Hz-20kHz	8Ω	100W	90dB	2 years	
		AP-CM1008D AVAILABLE JUNE 2017	In-ceiling	Round	Ø244mm	Ø223mm	✓	1mm	90mm	Steel	1.1kg	1"			8" polypropylene	50Hz-20kHz	8Ω	100W	90dB	2 years
		AP-CMX20DT AVAILABLE JUNE 2017	In-ceiling	Round	Ø250mm	Ø223mm	✓	1mm	87mm	Steel	1.45kg	1"			8" polypropylene	50Hz-20kHz	16Ω	100W	88dB	2 years
		AP-CMX20T	In-ceiling	Round	Ø244mm	Ø223mm	✓	15mm	87mm	Aluminium	1.4kg	1"			8" polypropylene	50Hz-20kHz	16Ω	100W	88dB	2 years
		AP-CMX20T-BL	In-ceiling	Round	Ø244mm	Ø223mm	✓	15mm	87mm	Aluminium	1.4kg	1"			8" polypropylene	50Hz-20kHz	16Ω	100W	88dB	2 years
	Network Audio Visual www.networkav.com.au Superbox www.superbox.co.nz	IC8.2	In-ceiling	Round, Square	Ø280mm	Ø244mm	✓	1mm	120mm	Powder-coated steel	3kg	1" silk		Poly-mica	45Hz-22kHz	6Ω	10-150W	89dB	5 years	
		IC8.3	In-ceiling	Round, Square	Ø280mm	Ø244mm	✓	1mm	115mm	Powder-coated steel	3kg	2 x 1" silk		Poly-mica	45Hz-22kHz	8Ω	10-150W	89dB	6 years	
	Hills www.hills.com.au www.hills.co.nz	QF8CS	In-ceiling	Round	Ø280mm	Ø245mm	✓	17.5mm	245mm	Powder-coated steel	1.4kg	Twin cone		8"	80Hz-20kHz	100V	15W	90dB	5 years	
		QFC8CS	In-ceiling	Round	Ø282mm	Ø248mm	✓		98mm	Powder-coated steel	1.6kg	25mm soft dome		8"	60Hz-20kHz	100V	30W	94dB	5 years	
		QF80CS	In-ceiling	Round	Ø308mm	Ø272mm	✓		244mm	Powder-coated steel	5.65kg	20mm aluminium dome		8"	50Hz-20kHz	16Ω or 100V	80W	90dB	5 years	
	Bang & Olufsen ANZ www.bang-olufsen.com	CELESTIAL BOC86	In-ceiling	Round, Square	Ø244mm	Ø220mm			142mm	Steel, Aluminium		25mm silk DPSD	102mm	203mm glass fibre	34Hz-20kHz	6Ω	50-175W			
		CELESTIAL BOC82	In-ceiling	Round, Square	Ø244mm	Ø220mm			105mm	Steel, Aluminium		25mm silk DPSD		203mm IMG	38Hz-20kHz	6Ω	50-125W			
		CELESTIAL BOC82DT/ SUR	In-ceiling	Round, Square	Ø244mm	Ø220mm			109mm	Steel, Aluminium		25mm silk DPSD		203mm IMG	38Hz-20kHz	6Ω	50-125W			
	Bose www.bose.com.au www.bose.co.nz	VIRTUALLY INVISIBLE 891	In-wall	Rectangular	333 x 239mm	295 x 201mm	✓		99mm	Aluminium	2.3kg	2 x 1"		18cm						
Bowers & Wilkins	Convoy International www.bowers-wilkins.com.au B&W Loudspeakers www.bwspeakers.co.nz	CCM382	In-ceiling	Round, Square	Ø290mm	Ø249mm	✓	6mm	85mm	Steel	4.3kg	Ø25mm soft dome	Ø200mm polypropylene mid/bass		45Hz-30kHz	8Ω	80W	90dB	5 years	
		CCM684	In-ceiling	Round, Square	Ø290mm	Ø250mm	✓	5mm	133mm	Steel	7.5kg	Ø25mm soft dome	Ø200mm glass fibre mid/bass		35Hz-35kHz	8Ω	25-130W	88dB	5 years	
		CCM683	In-ceiling	Round, Square	Ø290mm	Ø250mm	✓	5mm	133mm	Steel	8.7kg	Ø25mm swirl-loaded aluminium dome	Ø200mm blue Kevlar cone bass/ midrange		35Hz-50kHz	8Ω	25-130W	88dB	5 years	
		CCM682	In-ceiling	Round, Square	Ø290mm	Ø250mm	✓	5mm	133mm	Steel	8.9kg	Ø25mm swirl-loaded aluminium dome	Ø200mm blue Kevlar cone bass/ midrange		35Hz-50kHz	8Ω	25-130W	89dB	5 years	
		CCM CINEMA 7	In-ceiling	Round, Square	Ø290mm	Ø249mm	✓	5mm	128mm	Steel	4.1kg	Ø25mm swirl-loaded aluminium dome	Ø180mm blue Kevlar cone bass/ midrange		45Hz-50kHz	8Ω	25-130W	88dB	5 years	
		CCM 8.5	In-ceiling	Square	351 x 351mm	331 x 331mm	✓	6mm	177mm	Steel	7.1kg	Ø25mm carbon braced aluminium dome	Ø180mm blue Kevlar cone bass/ midrange		35Hz-40kHz	8Ω	120W	88dB	5 years	
		CWM 8.5	In-wall	Rectangular	411 x 247mm	395 x 231mm	✓	6mm	90mm	Steel	5.1kg	Ø25mm carbon braced aluminium dome	Ø180mm blue Kevlar cone bass/ midrange		35Hz-40kHz	8Ω	120W	89dB	5 years	
	Hills www.hills.com.au www.hills.co.nz	D8	In-ceiling	Round	335mm	Ø311mm	✓	12mm	207.4mm	Powder-coated steel	7.4kg	1.25" exit compression driver		8"	60Hz-22kHz	8Ω	150W	95dB	5 years	
		C8	In-ceiling	Round	Ø287mm	Ø263mm	✓	12mm	191.8mm	Powder-coated steel	3.8kg	¾" exit compression driver		8"	65Hz-13.5kHz	8Ω	60W	91dB	5 years	
	Advance Audio Australia www.advanceaudio.com.au TechStyle www.techstyle.co.nz	DT8LCR	In-wall	Rectangular	350.8 x 250.7mm	323.9 x 222.3mm	✓		95.3mm	Aluminium	2.72kg	1 pivoting		200mm	27Hz-30kHz	8Ω		89dB	5 years	
	Radio Parts www.radioparts.com.au Digital World www.digitalworld.net.nz	RCS800	In-ceiling	Round	Ø245mm	Ø217mm	✓		98mm	Aluminium	5kg	1" silk dome NEO swivel tweeter	8" polypropylene		45Hz-20kHz	8Ω	200W		5 years	
		SS82W	In-ceiling	Round	Ø282mm	Ø244mm	✓		147.5mm	Aluminium	4.4kg	1" silk dome compression tweeter	8" wide surround polypropylene cone woofer		30Hz-30kHz	8Ω	300W		5 years	
		CM800	In-ceiling	Round	Ø293mm	Ø250mm	✓		102mm	Aluminium	4.4kg	1" adjustable silk dome tweeter	8" low mass poly-mica		45Hz-21kHz	8Ω	125W		5 years	
		ECSS582	Both	Round, Square	Ø285mm	Ø245mm	✓		147.5mm	Aluminium	4.5kg	1" silk dome swiveling compression tweeter	8" wide surround woofer with polypropylene cone		30Hz-30kHz	8Ω	300W		5 years	
		EWS800	In-wall	Square	349 x 248mm	326 x 224mm	✓		103mm	Aluminium	5.3kg	1" silk dome compression tweeter	8" low mass stiff Kevlar cone		30Hz-20kHz	8Ω	500W		5 years	
		R800	Both	Round, Square	Ø270mm	Ø240mm	✓		116mm	Aluminium	4kg	1" silk dome swivel NEO tweeter	8" polypropylene		45Hz-20kHz	8Ω	200W		5 years	
		CM8DUAL	In-ceiling	Round	Ø292mm	Ø241.3mm	✓		114.3mm	Aluminium	3.375kg	Dual 20mm silk dome swiveling neodymium tweeters	8" low mass woven glass fibre cone		30Hz-21kHz	8Ω	400W		5 years	







8 INCH SPEAKER SHOWDOWN

MANUFACTURER	DISTRIBUTORS	MODEL NUMBER	IN-WALL/ IN-CEILING	SHAPE	DIMENSIONS	CUT-OUT DIMENSIONS	PAINTABLE FACADE	BEZEL WIDTH	SPEAKER DEPTH	GRILL MATERIAL	SHIPPING WEIGHT	TWEETER	MIDRANGE	WOOFER	FREQUENCY RESPONSE	NOMINAL IMPEDANCE	POWER HANDLING	SENSITIVITY (2.83V @1M)	WARRANTY	
 Electro-Voice	Midwich www.midwich.com.au www.midwich.co.nz	C8.2LP	In-ceiling	Round	Ø303mm	Ø272mm	✓	18mm	178mm	Steel	11kg	1x 25mm Ti mylar laminate	8" polypropylene cone		50Hz-20kHz	8Ω	75W	91dB	3 years	
		C8.2HC	In-ceiling	Round	Ø320mm	Ø322mm	✓	18mm	303mm	Steel	13.5kg	1x 25mm Ti mylar laminate	8" polypropylene cone plus waveguide		50Hz-20kHz	8Ω	75W	93dB	3 years	
		PC8.2	In-ceiling	Round	Ø327mm	Ø295mm	✓	16.5mm	324mm	Steel	20.23kg	1x 35mm compression driver	8" polypropylene cone		40Hz-20kHz	10Ω	200W	88dB	3 years	
 episode	Westan www.westan.com.au www.westan.net.nz	ES-350T-IC-8	In-ceiling	Round	Ø280mm	Ø246mm	✓	3mm	105mm	Steel		19mm teteron		200mm vacuum-formed polypropylene cone	50Hz-20kHz	8Ω	120W	87dB	Lifetime	
		ES-350T-IW-8	In-wall	Rectangular	381 x 288mm	348 x 229mm	✓	3mm	91.5mm	Steel		19mm teteron		200mm vacuum-formed polypropylene cone	50Hz-20kHz	8Ω	5-120W	87dB	Lifetime	
		ESS-1300T-IC8	In-ceiling	Round	Ø280mm	Ø246mm	✓	3mm	132mm	Steel		25mm silk dome adjustable		200mm injection-moulded polypropylene cone	38Hz-20kHz	8Ω	130W	90dB	Lifetime	
		ESS-1300T-IW8	In-wall	Rectangular	381 x 262mm	348 x 229mm	✓	3mm	91.5mm	Steel		25mm silk dome adjustable		200mm injection-moulded polypropylene cone	38Hz-20kHz	8Ω	130W	90dB	Lifetime	
		ESS-1500T-IC8	In-ceiling	Round	Ø280mm	Ø246mm	✓	3mm	132mm	Steel		25mm silk dome adjustable with vacuum-deposited titanium		200mm polypropylene with vacuum-deposited titanium	38Hz-20kHz	8Ω	130W	90dB	Lifetime	
		ESS-1500T-IW8	In-wall	Rectangular	381 x 287mm	348 x 229mm	✓	3mm	91.5mm	Steel		25mm silk dome adjustable with vacuum-deposited titanium		200mm polypropylene with vacuum-deposited titanium	38Hz-20kHz	8Ω	130W	90dB	Lifetime	
		ESS-1500T-ICSURR-8	In-ceiling	Round	Ø280mm	Ø246mm	✓	3mm	132mm	Steel		2 x 25mm silk dome adjustable with vacuum-deposited titanium		200mm polypropylene with vacuum-deposited titanium	38Hz-20kHz	8Ω	130W	90dB	Lifetime	
		ESS-1700T-IC8	In-ceiling	Round	Ø280mm	Ø246mm	✓	3mm	132mm	Steel		25mm pure titanium		200mm honeycomb fibreglass Nomex cone	34Hz-20kHz	8Ω	160W	91dB	Lifetime	
		ESS-1700T-IW8	In-wall	Rectangular	381 x 287mm	348 x 249mm	✓	3mm	91.5mm	Steel		25mm pure titanium		200mm honeycomb fibreglass Nomex cone	34Hz-20kHz	8Ω	160W	91dB	Lifetime	
ESS-1700T-ICSURR-8	In-ceiling	Round	Ø280mm	Ø246mm	✓	3mm	132mm	Steel		2 x 25mm pure titanium Bi/Di tweeter		200mm honeycomb fibreglass Nomex cone	34Hz-20kHz	8Ω	140W	91dB	Lifetime			
 FOCAL THE SPIRIT OF SOUND	N.A. Distributors www.focalloudspeakers.com KJ Distributors www.focalnz.co.nz	300 ICW 8	Both	Round, Square	Ø299mm	Ø264mm	✓		122mm	Metal Mesh	5.1kg	250mm Al/Mg alloy inverted dome with Poron suspension		210mm with Flax cone	48Hz-28kHz	8Ω	25-150W	90dB	2 years	
 inDESIGN	National Audio Systems nationalaudio.com.au	EZ8-15MK3	In-ceiling	Round	Ø275mm	Ø245mm	✓	15mm	82mm	Painted steel	2.3kg	13mm silk tweeter		8" treated paper cone	50Hz-20KHz	8Ω	40W	88dB	5 years	
 James LOUDSPEAKERS	Convergent Technologies www.c-t.com.au Atlantic Audio www.atlanticaudio.co.nz	FXCQ820R/S	In-ceiling	Round, Square	Ø274mm	Ø257.45mm	✓		149mm	Aluminium		4 x 19mm aluminium		203mm aluminium	65Hz-24kHz	8Ω	50-250W	93dB	10 years	
		QXC820R/S	In-ceiling	Round, Square	Ø274mm		✓		149mm	Aluminium			4 x 19mm aluminium		203mm aluminium	60Hz-24kHz	8Ω	50-250W	93dB	10 years
		"QXC8S-R/S SUBWOOFER"	In-ceiling	Round, Square	275 x 191mm		✓		191mm	Aluminium					203mm aluminium	38Hz-150Hz	8Ω	100-300W	86dB	5 years
		QX820	In-wall	Rectangular	433 x 282mm		✓		98mm	Aluminium			4 x 19mm aluminium		203mm aluminium	65Hz-24kHz	8Ω	50-300W	93dB	10 years
		QX830	In-wall	Rectangular	660 x 282mm		✓		98mm	Aluminium			4 x 19mm aluminium		203mm aluminium	60Hz-24kHz	8Ω	50-300W	93dB	10 years
		806BE	In-wall	Rectangular	812 x 329mm	730.25 x 254mm	✓		98mm	Cloth			4 x 25mm beryllium		2 x 203mm aluminium	45Hz-40kHz	8Ω	50-300W	96dB	10 years
		808BE	In-wall	Rectangular	1,286 x 329mm		✓		98mm	Cloth			4 x 25mm beryllium	2 x 165mm neodymium	2 x 203mm aluminium	45Hz-40kHz	4Ω	50-300W	98dB	10 years
		812BE	In-wall	Rectangular	1,905 x 445mm		✓		98mm	Cloth			4 x 25mm beryllium	4 x 165mm neodymium	4 x 203mm aluminium	40Hz-40kHz	8Ω	50-300W	102dB	10 years
		FX8-S SUBWOOFER	In-wall	Rectangular	483 x 284.5mm		✓		98mm	Aluminium					203mm aluminium active, 203mm passive	45Hz-40kHz	4Ω	50-300W	98dB	5 years
800PTM SUBWOOFER	Both	Rectangular	279.5 x 254mm		✓		384mm	Aluminium					203mm aluminium	28Hz-120Hz	8Ω	150-300W	88dB	5 years		
 Jamo Danish Sound Design	Convergent Technologies www.c-t.com.au Atlantic Audio www.atlanticaudio.co.nz	FXCQ820R/S	In-ceiling	Round, Square	Ø274mm	Ø257.45mm	✓		149mm	Aluminium		4 x 19mm aluminium		203mm aluminium	65Hz-24kHz	8Ω	50-250W	93dB	10 years	
		QXC820R/S	In-ceiling	Round, Square	Ø274mm		✓		149mm	Aluminium			4 x 19mm aluminium		203mm aluminium	60Hz-24kHz	8Ω	50-250W	93dB	10 years
		"QXC8S-R/S SUBWOOFER"	In-ceiling	Round, Square	275 x 191mm		✓		191mm	Aluminium					203mm aluminium	38Hz-150Hz	8Ω	100-300W	86dB	5 years
		QX820	In-wall	Rectangular	433 x 282mm		✓		98mm	Aluminium			4 x 19mm aluminium		203mm aluminium	65Hz-24kHz	8Ω	50-300W	93dB	10 years
		QX830	In-wall	Rectangular	660 x 282mm		✓		98mm	Aluminium			4 x 19mm aluminium		203mm aluminium	60Hz-24kHz	8Ω	50-300W	93dB	10 years
		806BE	In-wall	Rectangular	812 x 329mm	730.25 x 254mm	✓		98mm	Cloth			4 x 25mm beryllium		2 x 203mm aluminium	45Hz-40kHz	8Ω	50-300W	96dB	10 years
		808BE	In-wall	Rectangular	1,286 x 329mm		✓		98mm	Cloth			4 x 25mm beryllium	2 x 165mm neodymium	2 x 203mm aluminium	45Hz-40kHz	4Ω	50-300W	98dB	10 years

8 INCH SPEAKER SHOWDOWN

MANUFACTURER	DISTRIBUTORS	MODEL NUMBER	IN-WALL/ IN-CEILING	SHAPE	DIMENSIONS	CUT-OUT DIMENSIONS	PAINTABLE FACADE	BEZEL WIDTH	SPEAKER DEPTH	GRILL MATERIAL	SHIPPING WEIGHT	TWEETER	MIDRANGE	WOOFER	FREQUENCY RESPONSE	NOMINAL IMPEDANCE	POWER HANDLING	SENSITIVITY (2.83V @1M)	WARRANTY		
	Convergent Technologies www.c-t.com.au Atlantic Audio www.atlanticaudio.co.nz	812BE	In-wall	Rectangular	1,905 x 445mm		✓		98mm	Cloth		4 x 25mm beryllium	4 x 165mm neodymium	4 x 203mm aluminium	40Hz-40kHz	8Ω	50-300W	102dB	10 years		
		FX8-S SUBWOOFER	In-wall	Rectangular	483 x 284.5mm		✓		98mm	Aluminium				203mm aluminium active, 203mm passive	45Hz-40kHz	4Ω	50-300W	98dB	5 years		
		800PTM SUBWOOFER	Both	Rectangular	279.5 x 254mm		✓		384mm	Aluminium				203mm aluminium	28Hz-120Hz	8Ω	150-300W	88dB	5 years		
	Jands www.jands.com.au Jands NZ www.jands.co.nz	CONTROL 128W	In-wall	Rectangle	334 x 257mm	300 x 225mm	✓		102mm	Perforated steel	5.9kg	"25mm pure-titanium dome with cloth suspension on low-diffraction swivel-mount with -10 degree aimability"		200 mm polymer-coated aluminum cone, pure butyl rubber surround	30Hz-20 kHz	8Ω	240W	90dB	5 years		
		CONTROL 128WT	In-wall	Rectangle	334 x 257mm	300 x 225mm	✓		102mm	Perforated steel	7.8kg	"25mm pure-titanium dome with cloth suspension on low-diffraction swivel-mount with -10 degree aimability"		200 mm polymer-coated aluminum cone, pure butyl rubber surround	30Hz-20 kHz	8Ω	240W	90dB	5 years		
		CONTROL 18 C/T	In-ceiling	Round	ø307mm	ø282mm	✓			307mm	Perforated steel	17.7kg	25mm highly-damped treated-silk dome, Kapton voice coil, liquid cooling, wide dispersion waveguide		200mm with polypropylene cone, butyl rubber surround, anodised aluminum voice coil former, high temperature voice coil	58Hz-20kHz	8Ω	180W	92 dB	5 years	
		CONTROL 19 CS	In-ceiling	Round	345 x 345mm	ø305mm	✓			318mm	Perforated steel	12.7kg			200mm polypropylene cone. 38mm coil on aluminum former	42Hz - 200Hz	8Ω	200W	95dB	5 years	
		CONTROL 19 CST	In-ceiling	Round	ø345mm	ø305mm	✓			318mm	Perforated steel	14.3kg			200mm polypropylene cone. 38mm coil on aluminum former	42Hz-200Hz	8Ω	200W	95dB	5 years	
		CONTROL 40CS/T	In-ceiling	Round	ø332mm	ø307mm	✓			332mm	Perforated steel	8.1kg			200mm with polypropylene cone, butyl rubber surround, copper-clad coil, vented aluminum former	32Hz-300Hz	8Ω	200W	95dB	5 years	
		CONTROL 328C	In-ceiling	Round	ø305mm	ø310mm	✓			305mm	Perforated steel	5.8kg	JBL 2412H-1 compression driver, 25mm voice coil		Kevlar reinforced cone, 50mm voice coil	45Hz-18kHz	8Ω	250W	93dB	5 years	
		CONTROL 328CT	In-ceiling	Round	ø305mm	ø310mm	✓			305mm	Perforated steel	6.7kg	JBL 2412H-1 compression driver, 25mm voice coil		Kevlar reinforced cone, 50mm voice coil	45Hz-18kHz	8Ω	250W	93dB	5 years	
	BD Imports www.jensenspeakers.com.au BD Imports NZ www.jensenspeakers.com.au	EHT-8	Both	Rectangular	380 x 260mm	341 x 221mm	✓		20mm	95mm	Steel	13kg	28mm silk dome		200mm polypropylene	50Hz-21kHz	6Ω	5-140W	91dB	5 years	
		ELITE-404	In-ceiling	Round	ø287.5mm	ø257mm	✓			26mm	120mm	Glass	15kg	28mm silk dome		200mm polypropylene	50Hz-21kHz	6Ω	5-140W	91dB	5 years
	Advance Audio Australia www.advanceaudio.com.au Avalon Audio www.avalon.co.nz	CI 200 QSA	In-wall	Square	273 x 273mm	238 x 238mm	✓		5mm	106mm	Aluminium	2.4kg	25mm Uni-Q		200mm	35Hz-34kHz	8Ω	10-150W	90dB	5 years	
		CI 200 QL	In-wall	Rectangular	369 x 273mm	334 x 238mm	✓			5mm	106mm	Aluminium	2.6kg	25mm Uni-Q		200mm	35Hz-34kHz	8Ω	10-150W	90dB	5 years
	Powermove Distribution www.powermove.com.au Sound Group Holdings www.soundgroup.co.nz	R-5800-W II	In-wall	Rectangular	527 x 298mm	374 x 235mm	✓		5mm	95mm	Aluminium	3.6 kg	25mm titanium dome	152mm Tractrix horn	203mm ceramic	40Hz-23kHz	8Ω	50-200W	94dB	5 years	
		PRO-7800-S-THX	In-wall	Rectangular	527 x 298mm	483 x 298mm	✓		5mm	94mm	Aluminium	7.9 kg	2 x 25mm titanium dome neodymium		200mm aluminium cone	80Hz-20kHz	8Ω	100-400W	90dB	5 years	
		PRO-7800-L-THX	In-wall	Rectangular	527 x 298mm	527 x 298mm	✓		5mm	94mm	Aluminium	7.9 kg	25mm titanium dome		200mm aluminium cone	80Hz-20kHz	8Ω	150-600W	91dB	5 years	
		CDT-5800	In-wall	Round	ø279.4mm	ø248.9mm	✓			5mm	137mm		3.36kg	25mm titanium diaphragm		200mm ceramic	49Hz-23kHz	8Ω	50-200W	95dB	5 years
		CDT-3800-C II	In-wall	Round	ø279.4mm	ø248.9mm	✓			5mm	137mm		3.31kg	25mm aluminium diaphragm		200mm IMG cone	56Hz-23kHz	8Ω	50-200W	92dB	5 years
		CDT-2800-C II	In-wall	Round	ø279.4mm	ø248.9mm	✓			5mm	137mm		3.2kg	25mm silk		200mm polypropylene	65Hz-20kHz	8Ω	50-200W	93dB	5 years
		R-2800-CSM II	In-wall	Round	ø279.4mm	ø248.9mm	✓			5mm	114mm		3.58kg	2 x 191mm silk		200mm polypropylene	52Hz-20kHz	8Ω	50-200W	94dB	5 years
		R-1800-C	In-wall	Round	ø279.4mm	ø248.9mm	✓			5mm	114mm		2.6kg	25mm polymer		200mm polypropylene	56Hz-20kHz	8Ω	40-160W	89dB	5 years
	Krix Loudspeakers www.krix.com	STRATOSPHERIX AS	In-ceiling	Round	ø295mm	ø248mm	✓		5mm	182mm	Stainless steel	6kg	45mm mylar dome compression driver		200mm curvilinear polypropylene driver	45Hz-20kHz	6Ω	20-200W	93dB	5 years	
	Audio Active www.audioactive.com.au Capisco www.capisco.co.nz	VANQUISH	In-ceiling	Round	ø365mm	ø333mm	✓		155mm	Steel	7.3kg	32mm x 61mm folded motion	2 x 89mm aluminium	203mm aluminium cone	37Hz-25kHz	4Ω	20-300W	93dB	5 years		
	Synergy Audio Visual www.synergyaudio.com Sound Group Holdings www.soundgroup.co.nz	CS100	In-ceiling	Round	ø316mm	ø270mm	✓		52mm	141mm	Steel	4.8kg	25mm VF aluminium dome	89mm neo copolymer cone	203mm DCD copolymer cone	48Hz-22kHz	8Ω	50-200W	89dB	5 years	
		WS350	In-wall	Rectangular	597 x 355mm	572 x 337mm	✓		15mm	93mm	Steel	14.5kg	5x 25mm soft dome	102mm polypropylene cone	203mm LD/HP poly cone	60Hz-20kHz	4Ω	50-200W	85dB	5 years	
	Wavetrain Distribution www.wavetrain.com.au Denco Audio www.dencoaudio.co.nz	DSP320	Both	Square	300 x 300mm		✓		3mm	102mm	Powder-coated steel	10kg	85mm wide range	oval bass driver	20Hz-20kHz		160W	106dB	5 years		
		DSP520	Both	Rectangular	800 x 203mm		✓		3mm	102mm	Powder-coated steel	10kg	85mm wide range	140mm	20Hz-20kHz		250W	114dB	5 years		
		DSP640	Both	Rectangular	1,230 x 203mm		✓		3mm	102mm	Powder-coated steel	15kg	2 x 85mm wide range	2 x 140mm	20Hz-20kHz		250W	118dB	5 years		
	Qualifi www.qualifi.com.au	IW-285	Both	Rectangular	622 x 312mm	580 x 270mm	✓		95mm	Aluminium	11kg			2 x 203mm	28Hz-20kHz	4Ω			6 years		

8 INCH SPEAKER SHOWDOWN

MANUFACTURER	DISTRIBUTORS	MODEL NUMBER	IN-WALL/ IN-CEILING	SHAPE	DIMENSIONS	CUT-OUT DIMENSIONS	PAINTABLE FACADE	BEZEL WIDTH	SPEAKER DEPTH	GRILL MATERIAL	SHIPPING WEIGHT	TWEETER	MIDRANGE	WOOFER	FREQUENCY RESPONSE	NOMINAL IMPEDANCE	POWER HANDLING	SENSITIVITY (2.83V @1M)	WARRANTY	
	Convergent Technologies www.c-t.com.au	C82	In-ceiling	Round	Ø254mm	Ø244mm	✓		117mm	Aluminium	4kg	25mm aluminium		203mm aluminium	50Hz-22kHz	8Ω	50-100W	89dB	10 years	
	Qualifi www.qualifi.com.au Wildash Audio www.wildash.co.nz	NICM8MP	In-ceiling	Round	Ø289mm	Ø248mm			105mm	Aluminium	2.9kg	25mm ultrasilk soft-dome pivot		203mm glass fibre	50Hz-21kHz	8Ω	10-140W		Lifetime	
		NICM8PR	In-ceiling	Round	Ø289mm	Ø248mm			105mm	Aluminium	2.9kg	25mm teteron dome pivot		203mm glass fibre	48Hz-21kHz	8Ω	10-140W		Lifetime	
		NICM8HD	In-ceiling	Round	Ø289mm	Ø248mm			105mm	Aluminium	3kg	25mm teteron dome pivot		203mm	48Hz-21kHz	8Ω	10-160W		Lifetime	
		NICM8SI	In-ceiling	Round	Ø281mm	Ø248mm			105mm	Aluminium	3kg	2 x 25mm teteron dome pivot		203mm glass fibre	55Hz-21kHz	8Ω	10-130W		Lifetime	
		NIDS8PR	In-ceiling	Round	Ø285mm	Ø248mm			136mm	Aluminium	2.9kg	25mm teteron dome pivot		38mm	203mm pivoting glass fibre	48Hz-21kHz	8Ω	10-140W		Lifetime
		NIDS8HD	In-ceiling	Round	Ø285mm	Ø248mm			136mm	Aluminium	2.9kg	25mm		38mm	203mm pivoting	48Hz-21kHz	8Ω	10-160W		Lifetime
		NIDS8FX	In-ceiling	Round	Ø285mm	Ø248mm			136mm	Aluminium	3kg	2 x 25mm			203mm pivoting	48Hz-21kHz	8Ω	10-160W		Lifetime
		NIHD8R	In-wall	Rectangular	362 x 260mm	333 x 232mm		23mm	91mm	Aluminium	7.7kg	25mm teteron		203mm TCC	50Hz-21kHz	6Ω	10-150W	89dB	Lifetime	
	NAS Australia www.nasaustralia.com.au	SPKNL830IC	In-ceiling	Round	Ø273mm	Ø244mm	✓	20mm	120mm	Aluminium	7kg	1" mylar dome	3" PP cone with mica	8" PP cone	45Hz-22kHz	4Ω/8Ω	10-150W	89dB	1 year	
		SPKNL830ICLP	In-ceiling	Round	Ø273.5mm	Ø244mm	✓	5mm	131.5mm	Steel	7kg	1" mylar dome	3" PP cone with mica	8" PP cone	45Hz-22kHz	4Ω/8Ω	10-150W	89dB	1 year	
		SPKNLPR800IC	In-ceiling	Round	Ø273.5mm	Ø244mm	✓	5mm	139mm	Steel	7kg	1" titanium dome		8" Kevlar cone	45Hz-22kHz	4Ω/8Ω	10-150W	90dB	1 year	
	Altronic www.altronic.com.au	C 0852	In-ceiling	Round	Ø281mm	Ø245mm	✓	5mm	141mm	Powder-coated aluminium	7.9kg	25mm titanium		200mm Kevlar	60Hz-20kHz	8Ω	150W	85dB	1 year	
		C0857	In-ceiling	Round	Ø280mm	Ø247mm	✓	20mm	115mm	Powder-coated aluminium	7.4kg	25mm aluminium		200mm carbon fibre/glass	50Hz-20kHz	8Ω	120W	91dB	1 year	
		C0884	In-ceiling	Round	Ø280mm	Ø248mm	✓	20mm	190mm	Powder-coated aluminium	7.25kg	25mm silk dome		200mm polypropylene	50Hz-20kHz	8Ω	100W	89dB	1 year	
	Synergy Custom www.synergycustom.com SmartTech Distribution www.smarttechdistribution.co.nz	P80	In-ceiling	Round	Ø273mm	Ø247mm	✓		96mm	Steel	5.2kg	25mm silk		203mm polypropylene	38Hz-20kHz	8Ω	5-100W	88dB	Lifetime	
		P80DT	In-ceiling	Round	Ø273mm	Ø247mm	✓		96mm	Steel	2.7kg	2x 25mm silk		203mm polypropylene	38Hz-20kHz	8Ω	5-100W	88dB	Lifetime	
		D80	In-ceiling	Round	Ø244mm	Ø222mm	✓		92mm	Steel	2.5kg	25mm silk		203mm polypropylene	38Hz-20kHz	8Ω	50-125W	89dB	Lifetime	
		D82	In-ceiling	Round	Ø244mm	Ø222mm	✓		108mm	Steel	2.5kg	25mm aluminium		203mm graphite	38Hz-20kHz	8Ω	50-125W	89dB	Lifetime	
		D82DT/SUR	In-ceiling	Round	Ø244mm	Ø222mm	✓		108mm	Steel	2.6kg	2x 25mm aluminium		203mm graphite	38Hz-20kHz	8Ω	50-125W	89dB	Lifetime	
		D84	In-ceiling	Round	Ø244mm	Ø222mm	✓		187mm	Steel	4.4kg	25mm aluminium		102mm graphite	203mm graphite	36Hz-20kHz	8Ω	50-150W	89dB	Lifetime
		D86	In-ceiling	Round	Ø244mm	Ø222mm	✓		187mm	Steel	5.2kg	25mm silk DPSD		102mm glass fibre	203mm glass fibre	34Hz-20kHz	8Ω	50-175W	90dB	Lifetime
		D88	In-ceiling	Round	Ø244mm	Ø222mm	✓		187mm	Steel	5.7kg	25mm silk DPSD		102mm Kevlar	203mm Kevlar	30Hz-20kHz	8Ω	50-200W	90dB	Lifetime
	Audio Active www.audioactive.com.au Sound Group Holdings www.soundgroup.co.nz	H80-R	In-ceiling	Round	Ø265mm	Ø238mm	✓		101mm	Steel	2kg	1" PTD dome		203mm mineral filled polypropylene cone	45Hz-20kHz	8Ω	15-90W	90dB	5 years	
		P80-R	In-ceiling	Round	Ø261mm	Ø234mm	✓		114mm	Steel	3kg	1" X-PAL dome		203mm overmolded mineral filled polypropylene cone	39Hz-22kHz	8Ω	15-110W	92dB	5 years	
		P80-A	In-ceiling	Round	Ø320mm	Ø291mm	✓		155mm	Steel	4.1kg	1" X-PAL dome		203mm overmolded mineral filled polypropylene cone	39Hz-22kHz	8Ω	15-110W	93dB	5 years	
		P80-SM	In-ceiling	Round	Ø261mm	Ø234mm	✓		114mm	Steel	3.2kg	1" X-PAL dome		203mm overmolded mineral filled polypropylene cone	40Hz-22kHz	8Ω	15-110W	92.5dB	5 years	
		P80-1W	In-wall	Rectangular	321 x 234mm	293 x 205mm	✓		102mm	Steel	3.9kg	1" X-PAL dome		203mm overmolded mineral filled polypropylene cone	30Hz-22kHz	8Ω	15-150W	91.5dB	5 years	
		E80R	In-ceiling	Round	Ø261mm	Ø234mm	✓		114mm	Steel	2.9kg	1" X-PAL dome		203mm overmolded mineral filled polypropylene cone	37Hz-22kHz	8Ω	15-160W	93dB	5 years	
		E80-A	In-ceiling	Round	Ø261mm	Ø234mm	✓		114mm	Steel	2.9kg	1" X-PAL dome		203mm overmolded mineral filled polypropylene cone	37Hz-22kHz	8Ω	15-160W	93dB	5 years	
		E80-1W	In-wall	Rectangular	321 x 234mm	293 x 205mm	✓		102mm	Steel	3.9kg	1" X-PAL dome		203mm overmolded mineral filled polypropylene cone	33Hz-22kHz	8Ω	15-180W	92dB	5 years	
		SIG - 1R	In-ceiling	Round	Ø226mm	Ø200mm	✓		100mm	Steel	1.6kg	25mm P-Be dome			210mm Co-Pal cone anodised solid aluminium phase plug	37Hz-45kHz	8Ω	15-225W	92dB	5 years
		SIG - 1.5R V3	In-ceiling	Round	Ø296mm	Ø270mm	✓		139mm	Steel	2kg	2 x 25mm P-Be dome			210mm Co-Pal cone anodised solid aluminium phase plug	37Hz-45kHz	8Ω	15-225W	92dB	5 years

8 INCH SPEAKER SHOWDOWN

MANUFACTURER	DISTRIBUTORS	MODEL NUMBER	IN-WALL/ IN-CEILING	SHAPE	DIMENSIONS	CUT-OUT DIMENSIONS	PAINTABLE FACADE	BEZEL WIDTH	SPEAKER DEPTH	GRILL MATERIAL	SHIPPING WEIGHT	TWEETER	MIDRANGE	WOOFER	FREQUENCY RESPONSE	NOMINAL IMPEDANCE	POWER HANDLING	SENSITIVITY (2.83V @1M)	WARRANTY	
PMC	Interdyn www.interdyn.com.au www.interdyn.co.nz	WAFER-IW2	Both	Square	575 x 355mm	575 x 355mm	✓	5mm	100mm	Aluminium	7.1kg	2 x 27mm soft dome	170mm		40Hz-25kHz	8Ω	5-200W	90dB	20 years	
polkaudio	Interdyn www.polkhome.com.au www.polkhome.co.nz	V80	Both	Round	Ø282.6mm	Ø238.1mm	✓	8mm	92mm	Aluminium	2.6kg	Aimable silk/polymer dome (1")	Dynamic Balance driver with polypropylene cone and rubber surround		30Hz-27kHz	8Ω	10-100W	90dB	3 years	
		V85	Both	Rectangular	220 x 365.1mm	203 x 323.8mm	✓	8mm	92mm	Aluminium	2.6kg	Silk/polymer dome	Dynamic Balance driver with polymer composite cone		30Hz-27kHz	8Ω	10-125W	90dB	3 years	
		70RT	Both	Round	Ø206.4mm	Ø165.1mm	✓	8mm	212.7mm	Aluminium	3.2kg	Silk/polymer dome	Dynamic Balance driver with mineral-filled polypropylene cone	Dynamic Balance woofer with mineral-filled polypropylene cone	34Hz-27kHz	8Ω	10-125W	90dB	3 years	
PROFICIENT Audio Bywireless	Audio Visual Revolution www.avrevolution.com.au Sound Group Holdings www.soundgroup.co.nz	C791	In-ceiling	Round	Ø283mm	Ø247mm	✓	1mm	115mm	Steel	7kg	25mm pivoting soft dome		8" polypropylene	36Hz-20kHz	8Ω	125W	92dB	10 years	
		C801	In-ceiling	Round	Ø283mm	Ø247mm	✓	1mm	115mm	Steel	8kg	25mm pivoting aluminium dome		8" graphite	28Hz-22kHz	8Ω	150W	92dB	10 years	
		C851	In-ceiling	Round	Ø283mm	Ø247mm	✓	1mm	120mm	Steel	9kg	25mm pivoting aluminium dome		8" Kevlar	28Hz-22kHz	8Ω	175W	92dB	10 years	
		C841	In-ceiling	Round	Ø283mm	Ø247mm	✓	1mm	116mm	Steel	4kg	25mm pivoting silk dome		8" graphite	40Hz-22kHz	8Ω	150W	92dB	10 years	
		C871	In-ceiling	Round	Ø283mm	Ø247mm	✓	1mm	116mm	Steel	5kg	25mm pivoting aluminium dome		8" Kevlar	28Hz-22kHz	8Ω	175W	92dB	10 years	
		C825TT	In-ceiling	Round	Ø283mm	Ø247mm	✓	1mm	116mm	Steel	4kg	2 x 25mm pivoting aluminium dome		Dual VC 8" graphite	28Hz-22kHz	8Ω	150W	92dB	10 years	
		IWS85	In-wall	Rectangular	522 x 298mm	346 x 212mm	✓	1mm	95mm	Steel	6kg			2 x 8" graphite	30Hz-120Hz	8Ω	200W		10 years	
		W802	In-wall	Rectangular	378 x 257mm	346 x 212mm	✓	1mm	95mm	Steel	7kg	25mm pivoting aluminium dome		8" graphite	28Hz-22kHz	8Ω	150W	92dB	10 years	
W852	In-wall	Rectangular	378 x 257mm	346 x 212mm	✓	1mm	110mm	Steel	8kg	25mm pivoting aluminium dome		8" Kevlar	28Hz-22kHz	8Ω	175W	92dB	10 years			
REDBACK	Altronics www.altronics.com.au	C2119	In-ceiling	Round	Ø228mm	Ø195mm	✓	34mm	68mm	Powder-coated aluminium	1kg	2-way coaxial PECC Cone		200mm PECC	50Hz-20kHz	8Ω	30W	90dB	1 year	
SONANCE	Amber Technology www.ambertech.com.au AVD www.avd.co.nz	VP88	In-wall	Rectangular	406 x 254mm	368 x 216mm	✓	4mm	98mm	Powder-coated steel	10kg	1" ceramic dome, Ferrofluid-cooled, pivoting, in acoustic back chamber	4" Carbon fibre/Rohacell laminated cone with a rubber surround, pivoting	8" Carbon fibre/Rohacell laminated cone with a rubber surround	30Hz-20kHz	6Ω	5-175W	91dB	Lifetime	
		VP86	In-wall	Rectangular	406 x 254mm	368 x 216mm	✓	4mm	98mm	Powder-coated steel	9kg	1" ceramic dome, Ferrofluid-cooled, pivoting, in acoustic back chamber	4" Kevlar/Nomex laminated cone with a rubber surround, pivoting	8" Kevlar/Nomex laminated cone with a rubber surround	34Hz-20kHz	8Ω	5-150W	91dB	Lifetime	
		VP82	In-wall	Rectangular	406 x 254mm	368 x 216mm	✓	4mm	98mm	Powder-coated steel	9kg	1" ceramic dome, Ferrofluid-cooled, pivoting, in acoustic back chamber	4" textured polypropylene cone with a rubber surround, pivoting	8" textured polypropylene cone with a rubber surround	38Hz-20kHz	8Ω	5-125W	90dB	Lifetime	
		VP88R	In-ceiling	Round, Square	Ø295mm	Ø257mm	✓	4mm	153.4mm	Powder-coated steel	10kg	1" ceramic dome, Ferrofluid-cooled, pivoting, in acoustic back chamber	4" Carbon fibre/Rohacell laminated cone with a rubber surround, pivoting	8" Carbon fibre/Rohacell laminated cone with a rubber surround, pivoting	30Hz-20kHz	6Ω	5-175W	91dB	Lifetime	
		VP86R	In-ceiling	Round, Square	Ø295mm	Ø257mm	✓	4mm	153.4mm	Powder-coated steel	9kg	1" powder-coated aluminium dome, Ferrofluid-cooled, pivoting, in acoustic back chamber	4" Kevlar/Nomex laminated cone with a rubber surround, pivoting	8" Kevlar/Nomex laminated cone with a rubber surround, pivoting	34Hz-20kHz	8Ω		91dB	Lifetime	
		VP82R	In-ceiling	Round, Square	Ø295mm	Ø257mm	✓	4mm	153.4mm	Powder-coated steel	9kg	1" cloth dome, Ferrofluid-cooled, pivoting, in acoustic back chamber	4" textured polypropylene cone with a rubber surround, pivoting	8" textured polypropylene cone with a rubber surround, pivoting	38Hz-20kHz	8Ω	5-125W	90dB	Lifetime	
		VP80R	In-ceiling	Round, Square	Ø295mm	Ø257mm	✓	4mm	95mm	Powder-coated steel	5.67kg	1" cloth dome, Ferrofluid-cooled		8" polypropylene cone with a rubber surround	42Hz-20kHz	8Ω	5-125W	90dB	Lifetime	
		VP86R SST SUR	In-ceiling	Round, Square	Ø295mm	Ø257mm	✓	4mm	149mm	Powder-coated steel	4.5kg	2 x 1" powder coated aluminium domes, Ferrofluid-cooled, in acoustic back chamber	2 x 3" Kevlar/Nomex laminated cone with a rubber surround	8" Kevlar/Nomex laminated cone with a rubber surround, dual voice coil, pivoting	34Hz-20kHz	8Ω	5-150W	91dB	Lifetime	
		PS-C83RT	In-ceiling	Round, Square	Ø281mm	Ø257mm	✓			250mm	Powder-coated steel	11.34kg	1" cloth dome, pivoting, Ferrofluid cooled		8" polypropylene cone, Butyl rubber surround	55Hz-20kHz	8Ω	160W	91dB	5 years
		PS-C83WRT	In-ceiling	Round, Square	Ø281mm	Ø257mm	✓			250mm	Powder-coated steel	8.61kg			8" polypropylene cone, Butyl rubber surround	50Hz-150Hz	8Ω	200W	89dB	5 years
SOUNDTUBE ENTERTAINMENT	National Audio Systems nationalaudio.com.au	CM82-EZS-II-(B/W)	In-ceiling	Round	Ø298.5mm	Ø266.7mm	✓	8.6mm	95.3 mm	Painted steel	4.1 Kg	1" silk		8" polypropylene cone	109Hz-18kHz	16Ω	64W	106dB	5 years	
		CM82-EZ-II-(B/W)	In-ceiling	Round	Ø298.5mm	Ø266.7mm	✓	5.1mm	190.5 mm	Painted steel	3.6 Kg	1" silk		8" polypropylene cone	73Hz-19kHz	8Ω	40W	103.5dB	5 years	
		CM-EZ-II-(B/W)	In-ceiling	Round	Ø273mm	Ø247.7mm	✓	5.1mm	190.5mm	Painted steel	3.6 Kg	1" silk		8" polypropylene cone	73Hz-19kHz	8Ω	40W	87.5dB	5 years	
		CM89-EZ-(B/W)	In-ceiling	Round	Ø298.5mm	Ø266.7mm	✓	8.6mm	203.2mm	Painted steel	4.5 Kg	1" titanium compression driver with waveguide		8" treated paper cone, cloth surround	119Hz-22kHz	8Ω	75W	112dB	5 years	
		CM800I-(B/W)	In-ceiling	Round	Ø374.9mm	Ø323.9mm	✓	27.4 mm	201.7 mm	Painted steel	17.7 kg	1" titanium compression driver with waveguide		8" treated paper cone, cloth surround	97Hz-22kHz	8Ω	125W	90dB	5 years	
		CM800D-(B/W)	In-ceiling	Round	Ø374.9mm	Ø323.9mm	✓	27.4 mm	316.5mm	Painted steel	10.8 Kg	1" titanium compression driver with waveguide		8" treated paper cone, cloth surround	73Hz-22kHz	8Ω	125W	90.5dB	5 years	
		CM890I-(B/W)	In-ceiling	Round	Ø374.9mm	Ø323.9mm	✓	27.4 mm	201.7 mm	Painted steel	19.4 Kg	1" titanium compression driver with waveguide		8" treated paper cone, cloth surround	80Hz-22kHz	8Ω	125W	93dB	5 years	
		CM890D-(B/W)	In-ceiling	Round	Ø374.9mm	Ø323.9mm	✓	27.4 mm	316.5mm	Painted steel	13.1 Kg	1" titanium compression driver with waveguide		8" treated paper cone, cloth surround	77Hz-22kHz	8Ω	125W	93dB	5 years	

8 INCH SPEAKER SHOWDOWN

MANUFACTURER	DISTRIBUTORS	MODEL NUMBER	IN-WALL/ IN-CEILING	SHAPE	DIMENSIONS	CUT-OUT DIMENSIONS	PAINTABLE FACADE	BEZEL WIDTH	SPEAKER DEPTH	GRILL MATERIAL	SHIPPING WEIGHT	TWEETER	MIDRANGE	WOOFER	FREQUENCY RESPONSE	NOMINAL IMPEDANCE	POWER HANDLING	SENSITIVITY (2.83V @1M)	WARRANTY	
	National Audio Systems nationalaudio.com.au	CM82-BGM-(B/W)	In-ceiling	Round	Ø298.5mm	Ø266.7mm	✓	8.6mm	203.2mm	Painted steel	4.5 Kg	1" silk		8" polypropylene cone	70Hz-18kHz	16Ω	64W	86dB	5 years	
		IPD-CM82-BGM-WH	In-ceiling	Round	Ø298.5mm	Ø266.7mm	✓	8.6mm	203.2mm	Painted steel	4.5 Kg	1" silk		8" polypropylene cone	80Hz-20kHz		40W	103dB	5 years	
	Avation www.avation.com.au Sound Group Holdings www.soundgroup.co.nz	PROFILE AIM 8 ONE	In-ceiling	Round	Ø280mm	Ø248mm	✓	1mm	146mm	Galvanised steel	4.02kg	1 x 25mm silk		203mm polypropylene	40Hz - 20kHz	8Ω	125W	88dB	Lifetime	
		PROFILE AIM 8 TWO	In-ceiling	Round	Ø280mm	Ø248mm	✓	1mm	146mm	Galvanised steel	4.02kg	1 x 25mm silk		203mm reinforced glass fibre	40Hz - 20kHz	8Ω	125W	89dB	Lifetime	
		PROFILE AIM 8 THREE	In-ceiling	Round	Ø280mm	Ø248mm	✓	1mm	146mm	Galvanised steel	4.02kg	1 x 25mm aluminium		203mm aluminium	37Hz - 20kHz	8Ω 6Ω 4Ω	150W	89dB	Lifetime	
		PROFILE AIM 8 FIVE	In-ceiling	Round	Ø280mm	Ø248mm	✓	1mm	146mm	Galvanised steel	4.32kg	1 x 25mm aluminium/magnesium		203mm kevlar	33Hz - 20kHz	8Ω 6Ω 4Ω	150W	91dB	Lifetime	
		PROFILE AIM WIDE 1	In-ceiling	Round	Ø280mm	Ø248mm	✓	1mm	165mm	Galvanised steel	4.32kg	2 x 19mm silk dome		2 x 51mm graphite	203mm graphite	40Hz - 20kHz	8Ω	125W	88dB	Lifetime
		PROFILE AIM WIDE 3	In-ceiling	Round	Ø280mm	Ø248mm	✓	1mm	165mm	Galvanised steel	4.32kg	2 x 19mm aluminium		2 x 51mm aluminium	203mm aluminium	40Hz - 20kHz	8Ω	150W	91dB	Lifetime
		PROFILE AIM 8 DT 3	In-ceiling	Round	Ø280mm	Ø248mm	✓	1mm	140mm	Galvanised steel	3.16kg	2 x 25mm aluminium			203mm aluminium	40Hz - 20kHz	8Ω	100W	92dB	Lifetime
		AIM 8-2 S2	In-ceiling	Round	Ø280mm	Ø250mm	✓	1mm	152mm	Galvanised steel	4.02kg	2 x 16mm, 2 x 19mm silk dome			203mm glass fibre	33Hz - 20kHz	8Ω	150W	87dB	Lifetime
		AIM 8-3 S2	In-ceiling	Round	Ø280mm	Ø250mm	✓	1mm	152mm	Galvanised steel	4.10kg	2 x 16mm, 2 x 19mm aluminium			203mm aluminium	35Hz - 20kHz	8Ω	175W	88dB	Lifetime
		AIM 8-5 S2	In-ceiling	Round	Ø280mm	Ø250mm	✓	1mm	152mm	Galvanised steel	4.28kg	2 x 16mm, 2 x 19mm aluminium/magnesium			203mm kevlar	37Hz - 20kHz	8Ω	175W	90dB	Lifetime
		AIM 8-DT3-S2	In-ceiling	Round	Ø280mm	Ø250mm	✓	1mm	152mm	Galvanised steel	4.24kg	2 x 16mm, 2 x 19mm aluminium			203mm aluminium	40Hz - 20kHz	8Ω	150W	90dB	Lifetime
		PRF CRS8-1	In-ceiling	Round	Ø303mm	Ø248mm	✓	1mm	114mm	Galvanised steel	2.90kg	1 x 25mm silk			203mm polypropylene	40Hz - 20kHz	8Ω	100W	90dB	Lifetime
		PRF CRS8-2	In-ceiling	Round	Ø303mm	Ø248mm	✓	1mm	114mm	Galvanised steel	3.36kg	1 x 25mm silk			203mm glass composite	40Hz - 20kHz	8Ω	100W	90dB	Lifetime
		PRF CRS8-3	In-ceiling	Round	Ø303mm	Ø248mm	✓	1mm	114mm	Galvanised steel	3.46kg	1 x 25mm aluminium			203mm aluminium	38Hz - 20kHz	8Ω	125W	90dB	Lifetime
		CRS-8 ZERO	In-ceiling	Round	Ø303mm	Ø248mm	✓	25mm	108mm	Galvanised steel	1.94kg	1 x 25mm silk			203mm graphite	30Hz - 120kHz	8Ω	100W	90dB	Lifetime
PRO-COM8	In-ceiling	Round	Ø329mm	Ø291mm	✓	25mm	236mm	Galvanised steel	8.1kg	1 x 25mm polyamide			203mm polypropylene	56Hz - 20kHz	8Ω, 100V	140W	88dB	Lifetime		
	Oceanic Distribution www.oceanicdistribution.com	VQ8	Both	Round, Square	Ø280mm	Ø250mm	✓	1mm	100mm	Steel	5.7kg	25mm silk dome		200mm Carbon Nomex	40Hz-20kHz	8Ω	125W	85dB	10 years	
		VR8-C	In-ceiling	Round	Ø280mm	Ø250mm	✓	22mm	108mm	Aluminium	6.4kg	25mm silk dome		200mm Carbon Nomex	40Hz-20kHz	8Ω	120W	85dB	10 years	
	Network Audio Visual www.networkav.com.au	NFC83A	In-ceiling	Round, Square	Ø285mm	Ø248mm	✓	1mm	128mm	Steel	4 kg	1" titanium		204mm Kevlar Trueform	36Hz-20kHz	8Ω	5-175W	89dB	10 years	
		NFC81	In-ceiling	Round, Square	Ø285mm	Ø248mm	✓	1mm	112mm	Steel	3kg	1" silk		Polypropylene trueform	40Hz-20kHz	8Ω	5-125W	88dB	10 years	
	Control4 www.control4.com	ZTS-50280-1	Both	Round, Square	Ø271mm	242 x 242mm	✓	2mm	111mm	Steel	6.8kg	1"		8.5" carbon fibre composite	40Hz-20kHz	8Ω	25-125W	88dB	5 years	
	Advance Audio Australia www.advanceaudio.com.au AVA Pacific www.avapacific.co.nz	GPW-8	In-wall	Rectangular	370 x 264mm	340 x 234mm	✓		99mm	Aluminium		1" silk		200mm polypropylene	40Hz-20kHz	8Ω	5-125W	90dB	5 years	
	Audio Visual Revolution www.avrevolution.com.au	DC-8	In-ceiling	Round	Ø272mm	Ø241mm	✓	1.5mm	111mm	Steel	6kg	20mm pivoting soft dome		8" polypropylene	45Hz-20kHz	8Ω	125W	84dB	5 years	
		DW-8	In-wall	Rectangular	355 x 255mm	326 x 225mm	✓	1.5mm	94mm	Steel	6kg	20mm pivoting soft dome		8" polypropylene	45Hz-20kHz	8Ω	125W	84dB	5 years	
	Yamaha Music Australia au.yamaha.com Sound Group Holdings www.soundgroup.co.nz	NS-IC800W	In-ceiling	Round	Ø272mm	Ø245mm	✓	50mm	113.5mm	Powder-coated aluminium	5kg	1" fluid cooled soft dome type		20cm PP Mica cone	50Hz-28kHz	8Ω	50-140W	90dB	2 years	